

CR 鋰錳扣式電池

型號	標稱電壓 (V)	標稱容量 (mAh)	標準放電條件 (KΩ)	工作溫度 (°C)	最大尺寸 (mm)	重量 (g)
CR927	3	30	68	-20~60	φ9.5×2.7	0.6
CR1025	3	30	68	-20~60	φ10.0×2.5	0.7
CR1216	3	25	62	-20~60	φ12.5×1.6	0.7
CR1220	3	35	62	-20~60	φ12.5×2.0	0.8
CR1225	3	50	62	-20~60	φ12.5×2.5	0.9
CR1616	3	50	30	-20~60	φ16.0×1.6	1.2
CR1620	3	70	47	-20~60	φ16.0×2.0	1.3
CR1625	3	90	30	-20~60	φ16.0×2.5	1.8
CR1632	3	120	15	-20~60	φ16.0×3.2	2
CR2016	3	83	30	-20~60	φ20.0×1.6	2
CR2025	3	150	15	-20~60	φ20.0×2.5	2.6
CR2032	3	220	15	-20~60	φ20.0×3.2	3.2
CR2050	3	350	15	-20~60	φ20.0×5.0	4.5
CR2320	3	130	15	-20~60	φ23.0×2.0	3
CR2325	3	190	15	-20~60	φ23.0×2.5	3.3
CR2330	3	260	15	-20~60	φ23.0×3.0	4
CR2335	3	300	15	-20~60	φ23.0×3.5	4.3
CR2354	3	530	7.5	-20~60	φ23.0×5.4	6
CR2430	3	270	15	-20~60	φ24.5×3.0	4.5
CR2450	3	600	7.5	-20~60	φ24.5×5.0	6.9
CR2477	3	1000	4.7	-20~60	φ24.5×7.7	10.5
CR3032	3	500	7.5	-20~60	φ30.0×3.2	6.8