



# BR 锂氟化石墨扣式电池

型号	标称电压 (V)	标称容量 (mAh)	标准放电条件 (KΩ)	工作温度 (°C)	最大尺寸 (mm)	重量 (g)
BR1225	3	48	30	-40 ~ 85	φ12.5×2.5	0.8
BR1632	3	130	15	-40 ~ 85	φ16.0×3.2	1.7
BR2016	3	60	30	-40 ~ 85	φ20.0×1.6	1.6
BR2025	3	130	15	-40 ~ 85	φ20.0×2.5	2.4
BR2032	3	200	15	-40 ~ 85	φ20.0×3.2	3.0
BR2325	3	165	15	-40 ~ 85	φ23.0×2.5	3.2
BR2330	3	260	15	-40 ~ 85	φ23.0×3.0	3.5
BR2335	3	300	15	-20 ~ 60	φ23.0×3.5	4.3
BR2354	3	420	7.5	-40 ~ 85	φ23.0×5.4	6.2
BR2430	3	230	15	-40 ~ 85	φ24.5×3.0	4.2
BR2450	3	550	7.5	-40 ~ 85	φ24.5×5.0	6
BR2477	3	800	4.7	-40 ~ 85	φ24.5×7.7	9.6
BR3032	3	500	7.5	-40 ~ 85	φ30.0×3.2	5.5